

PRODUCT NUMBER	PRODUCT	SPECIFICATION	SPEC. NUMBER
#1106	OIL SPOT SEAL		#1106

**DESCRIPTION:**

A water based polymer designed to cover and promote adhesion over oil, grease, and gasoline spots or stains prior to the application of coal tar sealer on asphalt surfaces. Oil spot seal can be used on any asphalt surface, including parking lots, driveways, airport runways, traffic islands, golf cart paths, and etc. OSS is clear, when dry.

**SURFACE PREPARATION:**

The surface to be sealed should be properly repaired before being sealed. Any places where the asphalt does not have good structural integrity should be saw cut out and replaced before it is sealed. Oil Spot Seal is not designed to add any structural integrity to spots where petroleum products have softened the asphalt. Wipe up or scrape excessive build-up of oil, grease or gasoline spots. It is necessary that the spot to be sealed must be cleaned sufficiently to allow the OSS to adhere to the asphalt.

**MIXING:**

Reduce concentrated OSS 1 to 1 or 1 to 2 with water before applying to the oil spot. Mix OSS thoroughly after reducing with water to get it homogeneous.

**APPLICATION:**

Apply with brush, roller or spray unit. Allow to dry completely before applying sealer. Do not apply when ground temperature is below 50 F. Do not apply if rain is eminent or forecast.

**COVERAGE:**

Concentrated Oil Spot seal will cover 100 to 400 square feet per gallon depending on the severity of the spot being sealed and the porosity of the surface.

**GENERAL:**

Wash tools in water before the material has dried. Keep Oil Spot Seal from freezing. Do not store OSS in direct sunlight or where temperatures exceed 100 F.

**WARRANTY:**

The statements made on this technical bulletin are believed to be true and accurate, and are intended to provide a guide for approved construction practices. Asphalt Coatings Engineering does not make nor does it authorize any agent or representative to make any warranty, expressed or implied, concerning this material, as workmanship, weather, construction, equipment utilized and other variables affecting results are all beyond our control. ACE warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. In no event shall ACE be liable for any injury, loss or damage, either direct, incidental, special or consequential, however arising, in connection with material or equipment furnished or work performed. ACE shall not, in any manner, be liable for any defects, variations, or change in condition in the substructure over which its products are installed.

**ASPHALT COATINGS ENGINEERING  
851 H STREET  
WASCO, CA 93280  
661 758-3051  
800 542-3900**